

TECHNICAL DATA SHEET

WASAABII 200LM SWING MAXITRIM IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Adjustable 0° - 85°

Clip Ø43 mm - h = 45 mm

Material: Aluminium



Ref N° 1100 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro



Ref N° 1100 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco



Ref N° 1100 GREY

Grey
Grigio
Grau
Grijs
Gris
Gris



Ref N° 1100 MESSING

Brass
Otonne
Messing
Messing
Laiton
Latón



Ref N° 1100 BRONZE

Bronze
Bronzo
Bronze
Bronz
Bronze
Bronce



Ref N° 1101 00 001

Clip-on assessorly 1
Small ball

WASAABII SWING MAXITRIM IP54 200LM CRI 92

	2700°K	3000°K	
	REF N° 1154 27 931	REF N° 1154 27 831	

2 W - 200LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - - -
Requires remote LED driver - 700mA
Standard Perfectbeam 12°- Optional 8° beam
Ultra low glare (UGR < 13)

INTEGRAL LED DRIVER

REF N° 697 67 015 15W DIM 1-10V Ø40 x 149mm

REF N° 697 37 015 15W DIM DALI Ø40 x 149mm

REF N° 697 77 010 10W PHASE DIM Ø42 x 94mm

230V/50Hz - - - **CE** - IP20 - 700mA
fits through the opening of Ø43mm

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - - current controlled
 - **CE** - IP20 - 700mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W

1-10V DALI PUSH




REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 77 010 min 2W max 10W PHASE DIM

REF N° 697 77 020 min 11W max 20W PHASE DIM

230V/50Hz - - - current controlled
 - **CE** - IP20 - 700mA - dimmable



INSTALLATION KIT

REF N° 680 01 043 standard holesaw Ø 43 mm

BEAM ANGLES

STANDARD (included) beam angle 12°
REF N° 203 20 008 (option) beam angle 8°