

TECHNICAL DATA SHEET



ELLIPS 111 IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable ϕ 0° - 30°

364x364 mm

Material : CALCYT® plaster



ELLIPS 111 LED 3000LM CRI 80

REF N°	2700°K	3000°K	4000°K
on/off	259 26 040	259 26 140	259 26 240
phase DIM	259 66 040	259 66 140	259 66 240
DIM DALI	259 36 040	259 36 140	259 36 240

Xicato LED - 29,3W - 3000lm - 2 Step MacAdam
 - 230V/50Hz - - -
 Beam angle 36° (option 20°) - Incl LED driver
 h = 140 mm

ELLIPS 111 LED 2000LM CRI 80

REF N°	2700°K	3000°K	4000°K
on/off	259 25 040	259 25 140	259 25 240
phase DIM	259 75 040	259 75 140	259 75 240
DIM 1-10V	259 65 040	259 65 140	259 65 240
DIM DALI	259 35 040	259 35 140	259 35 240

Xicato LED - 19,5W - 2000lm - 2 Step MacAdam
 - 230V/50Hz - - -
 Beam 36° (option 20°) - Incl LED driver
 h = 140 mm

ELLIPS 111 LED 1300LM CRI 97

REF N°	2700°K	3000°K	4000°K
on/off	259 23 940	259 23 840	259 23 740
phase DIM	259 73 940	259 73 840	259 73 740
DIM 1-10V	259 63 940	259 63 840	259 63 740
DIM DALI	259 33 940	259 33 840	259 33 740

Xicato LED - 17,6W - 1300lm - 2 Step MacAdam
 - 230V/50Hz - - -
 Beam angle 36° (option 20°) - Incl LED driver
 h = 140 mm

ELLIPS 111 LED 2000LM CRI 97

REF N°	2700°K	3000°K	4000°K
on/off	259 25 940	259 25 840	259 25 740
phase DIM	259 75 940	259 75 840	259 75 740
DIM 1-10V	259 65 940	259 65 840	259 65 740
DIM DALI	259 35 940	259 35 840	259 35 740

Xicato LED - 22,3W - 2000lm - 2 Step MacAdam
 - 230V/50Hz - - -
 Beam angle 36° (option 20°) - Incl LED driver
 h = 140 mm

ELLIPS 111 AR

REF N° 259 13 100

QR-LP 111 - 100W - G53 - 12V -
 excl. transfo - - -
 h = 95 mm

ELLIPS 111 CDM

REF N° 259 19 070 CDM-TC - G8.5

REF N° 259 12 070 CDM-R - GX8.5

35W or 70W - 230V/50Hz - - excl. EVG
 h = 133 mm - - -

INSTALLATION KIT

- STANDARD** (included) installation system for ceiling 9 - 12 - 15 mm
- REF N° 259 99 025** installation system for gypsum ceiling 25 mm
- REF N° 259 99 030** installation system for gypsum ceiling 30 mm

BEAM ANGLES & OPTIONS

- STANDARD** (included) beam angle 36°
- REF N° 205 11 020** optional beam angle 20°
- REF N° 201 00 060** Frosted diffusor for 111 LED series