

TECHNICAL DATA SHEET


FRAME IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Fix (not adjustable) 0° - 0°

□ 324x522 mm

Material : CALCYT® plaster



FRAME LED WARMDIM 900LM 230VAC			
WARMDIM : DIMS FROM 3000°K TO 2000°K			
REF N° 109 73 600 phase DIM			
REF N° 109 63 600 DIM 1-10V			
REF N° 109 33 600 DIM DALI			
230V/50Hz - 12,8W - incl. line voltage driver ◇ - parallel wiring ▽ 0.2m E-CE - Ⓢ - 4 Step MacAdam - CRI 90 - B			

FRAME LED 800LM 230VAC			
REF N°	2200°K	2700°K	3000°K
phase DIM	109 71 500	109 71 000	109 71 100
DIM 1-10V	109 61 500	109 61 000	109 61 100
DIM DALI	109 31 500	109 31 000	109 31 100
230V/50Hz - 9,3W - incl. line voltage driver ◇ - parallel wiring ▽ 0.2m E-CE - Ⓢ - 2 Step MacAdam - CRI 90 - R9=75 - A			

FRAME LED 1000LM 230VAC			
REF N°	2700°K	3000°K	4000°K
phase DIM	109 72 000	109 72 100	109 72 200
DIM 1-10V	109 62 000	109 62 100	109 62 200
DIM DALI	109 32 000	109 32 100	109 32 200
230V/50Hz - 11W - incl. line voltage driver ◇ - parallel wiring ▽ 0.2m E-CE - Ⓢ - 2 Step MacAdam - CRI 90 - R9=75 - A			

FRAME LED 2000LM 230VAC			
REF N°	2700°K	3000°K	4000°K
phase DIM	109 74 000	109 74 100	109 74 200
DIM 1-10V	109 64 000	109 64 100	109 64 200
DIM DALI	109 34 000	109 34 100	109 34 200
230V/50Hz - 14,1W - incl. line voltage driver ◇ - parallel wiring ▽ 0.2m E-CE - Ⓢ - 2 Step MacAdam - CRI 80 - A			

Ready for installation in solid walls
Optional plasterkit for installation into gypsum walls

PLASTERKIT FRAME
REF N° 709 01 000 For mounting into gypsum walls

